

Capacities and Specifications

TECHNICAL SPECIFICATIONS

Item	Capacity	Ford part name or equivalent	Ford part number / Ford Specification
Brake fluid	Between MIN and MAX lines on reservoir	Motorcraft® High Performance DOT 3 Motor Vehicle Brake Fluid	PM-1-C / WSS-M6C62-A or WSS-M6C65-A1
Engine oil without cooler (with filter change)	8.5 quarts (8.0L)	Motorcraft® 5W-50 Full Synthetic Motor Oil	XO-5W50-QGT / WSS-M2C931-B
Engine oil with cooler (with filter change)			
Engine coolant ¹	21.1 quarts (20.0L)	Motorcraft® Orange Antifreeze/Coolant Prediluted	VC-3DIL-B (US) CVC-3DIL-B (Canada) / WSS-M97B44-D2
Intercooler coolant ¹	5.4 quarts (5.1L)		
Rear axle lubricant without cooler ²	4 pints (1.9L)	Motorcraft® SAE 75W-85 Premium Synthetic Hypoid Gear Lubricant	XY-75W85-QL / WSS-M2C942-A
Rear axle lubricant with cooler ²	6 pints (2.8L)		
Rear axle fluid friction modifier without cooler	4 oz. (118 ml)	Additive Friction Modifier	XL-3 EST-M2C118-A
Rear axle fluid friction modifier with cooler	6 oz. (177 ml)		
Fuel tank	16.0 gallons (60.5L)	—	—